



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : <b>A61B 10/00, 17/32, 17/22, 17/39</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 99/44506</b></p> <p>(43) International Publication Date: 10 September 1999 (10.09.99)</p>
<p>(21) International Application Number: PCT/US99/04471</p> <p>(22) International Filing Date: 2 March 1999 (02.03.99)</p> <p>(30) Priority Data:  60/076,973      3 March 1998 (03.03.98)      US  09/057,303      8 April 1998 (08.04.98)      US</p> <p>(71) Applicant: SENORX, INC. [US/US]; 13766 Alton Parkway #144, Irvine, CA 92618 (US).</p> <p>(72) Inventors: BURBANK, Fred, H.; 30982 Steeplechase Drive, San Juan Capistrano, CA 92675 (US). JONES, Michael, L.; 34441 Camino El Molino, Capistrano Beach, CA 92624 (US). LUBOCK, Paul; 30 Bethany, Laguna Niguel, CA 92677 (US).</p> <p>(74) Agent: STOUT, Donald, E.; Stout, Uxa, Buyan &amp; Mullins, LLP, 100 Pacifica #210, Irvine, CA 92618 (US).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p> <p><b>BEST AVAILABLE COPY</b></p>
<p>(54) Title: BREAST BIOPSY SYSTEM AND METHOD</p> <div data-bbox="397 1171 1177 1570"> </div> <p>(57) Abstract</p> <p>An apparatus and method are provided for precisely isolating a target lesion in a patient's body tissue, resulting in a high likelihood of "clean" margins about the lesion when it is removed for diagnosis and/or therapy. This approach advantageously will often result in the ability to both diagnose and treat a malignant lesion with only a single percutaneous procedure, with no follow-up percutaneous or surgical procedure required, while minimizing the risk of migration of possible cancerous cells from the lesion to surrounding tissue or the bloodstream. In particular, the apparatus comprises a biopsy instrument having a distal end adapted for entry into the patient's body, a longitudinal shaft, and a cutting element disposed along the shaft. The cutting element is actuatable between a radially retracted position and a radially extended position. Advantageously, the instrument is rotatable about its axis in the radially extended position to isolate a desired tissue specimen from surrounding tissue by defining a peripheral margin about the tissue specimen. Once the tissue specimen is isolated, it may be segmented by further manipulation of the cutting element, after which the tissue segments are preferably individually removed from the patient's body through a cannula or the like. Alternatively, the specimen may be encapsulated and removed as an intact piece.</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## BREAST BIOPSY SYSTEM AND METHOD

### Field of the Invention

The present invention relates to methods and devices for removing tissue samples, and more specifically to improved instruments and methods for acquiring soft body tissue.

### Background of the Invention

It is often desirable and frequently necessary to sample or remove a portion of tissue from humans and other animals, particularly in the diagnosis and treatment of patients with cancerous tumors, pre-malignant conditions, and other diseases or disorders.

5           Typically, in the case of cancer, particularly cancer of the breast, there is a great emphasis on early detection and diagnosis through the use of screening modalities, such as physical examination, and particularly mammography, which is capable of detecting very small abnormalities, often nonpalpable. When the physician establishes by means of a mammogram or other screening modality,  
10           such as ultrasound, that suspicious circumstances exist, a biopsy must be performed to capture tissue for a definitive diagnosis as to whether the suspicious lesion is cancerous. Biopsy may be done by an open or percutaneous technique. Open biopsy, which is an invasive surgical procedure using a scalpel and involving direct vision of the target area, removes the entire mass (excisional  
15           biopsy) or a part of the mass (incisional biopsy). Percutaneous biopsy, on the other hand, is usually done with a needle-like instrument through a relatively small incision, blindly or with the aid of an artificial imaging device, and may be either a fine needle aspiration (FNA) or a core biopsy. In FNA biopsy, individual cells or clusters of cells are obtained for cytologic examination and may be  
20           prepared such as in a Papanicolaou smear. In core biopsy, as the term suggests, a core or fragment of tissue is obtained for histologic examination which may be done via a frozen section or paraffin section.

The type of biopsy utilized depends in large part on circumstances present with respect to the patient, including the location of the lesion(s) within the body, and no single procedure is ideal for all cases. However, core biopsy is extremely useful in a number of conditions and is being used more frequently by the  
5 medical profession.

A very successful type of image guided percutaneous core breast biopsy instrument currently available is a vacuum-assisted automatic core biopsy device. One such successful biopsy device is shown and disclosed in U.S. Patent No. 5,526,822 to Burbank et al, expressly incorporated by reference herein. This  
10 device, known commercially as the MAMMOTOME® Biopsy System, which is available from Ethicon Endo-Surgery, Inc., a division of Johnson & Johnson, has the capability to actively capture tissue prior to cutting the tissue. Active capture allows for sampling through non-homogeneous tissues. The device is comprised of a disposable probe, a motorized drive unit, and an integrated vacuum source.  
15 The probe is made of stainless steel and molded plastic and is designed for collection of multiple tissue samples with a single insertion of the probe into the breast. The tip of the probe is configured with a laterally disposed sampling notch for capturing tissue samples. Orientation of the sample notch is directed by the physician, who uses a thumbwheel to direct tissue sampling in any direction  
20 about the circumference of the probe. A hollow cylindrical cutter severs and transports tissue samples to a tissue collection chamber for later testing.

While this type of system functions very well as a core biopsy device, there are occasions when it may be useful to have the capability of acquiring a relatively large intact tissue sample. One such core biopsy device is disclosed in  
25 U.S. Patent No. 5,111,828, to Kornberg et al., also expressly incorporated by reference herein. In the device disclosed by Kornberg et al., the tissue receiving port is disposed at the distal end of the device and is oriented axially rather than laterally. A disadvantage of this type of device, however, is the inability to acquire a tissue sample having a cross-section larger than that of the cannula  
30 through which the sample will be removed. Additionally, it is difficult, using

such a device, which obtains cylindrical shaped specimens, to determine whether an entire lesion of interest is being removed or whether a further procedure will be necessary. This is particularly true because most lesions of interest are typically spherical in shape, having a diameter of approximately 1 cm. The only way one can tell whether the entire lesion has been removed using the Kornberg technique is to remove and examine the specimen, determining whether each of the margins of the specimen is "clean", meaning that there is no evidence of lesion, or "dirty", meaning that lesion is evident right to the edge of the specimen. Of course, if one or more specimen margins is "dirty", it is almost a certainty that a portion of the lesion remains in the patient, and if the biopsy test results on the lesion are positive, a further surgical procedure will be indicated.

It would be desirable, therefore, to have an apparatus and method for isolating a target lesion, with a sufficient border around and beyond the lesion that the likelihood of "clean" margins is relatively high. It would further be advantageous to have an apparatus and method available for initially isolating the entire target lesion, by cutting a swath completely about the lesion to cut off its blood supply, after which a further procedure is undertaken to remove it from the patient's body. This approach would help to minimize the migration of possibly cancerous cells from the lesion to surrounding tissue or bloodstream during the removal procedure.

### **Summary of the Invention**

The present invention addresses the foregoing problems by providing such an apparatus and method for precisely isolating a target lesion, resulting in a high likelihood of "clean" margins. This advantageously will often result in the ability to both diagnose and treat a malignant lesion with only a single percutaneous procedure, with no follow-up percutaneous or surgical procedure required, while minimizing the risk of migration of possibly cancerous cells from the lesion to surrounding tissue or the bloodstream.

More particularly, in one aspect of the invention, a biopsy instrument is

provided for retrieving body tissue, which instrument has a longitudinal axis. The instrument comprises a distal end adapted for entry into a patient's body, a shaft disposed along the axis, and a cutting element disposed along the shaft. The cutting element is actuatable between a radially retracted position and a radially extended position. Advantageously, the instrument is rotatable about its axis in the radially extended position to isolate a desired tissue specimen from surrounding tissue by defining a peripheral margin about the tissue specimen. Once the tissue specimen is isolated, it may be segmented by further manipulation of the cutting element, after which the tissue segments are preferably individually removed from the patient's body through a cannula or the like. Alternatively, the specimen may be encapsulated and removed as an intact piece.

In another aspect of the invention, an instrument is provided for retrieving body tissue, having a longitudinal axis and comprising a distal end adapted for entry into a patient's body. The instrument further comprises an element for encapsulating a tissue specimen so that it may be withdrawn as a single unit from the patient's body. The encapsulating element preferably comprises a plurality of bands disposed along the instrument axis, each of which are actuatable between a radially retracted position and a radially extended position.

In yet another aspect of the invention, a method is disclosed for retrieving a tissue specimen from a patient's body, comprising the steps of inserting an instrument having a distal end, a longitudinal axis, and an axially disposed cutting element, into the patient's body, so that a distal end is disposed in a tissue region from which the tissue specimen is to be taken. The cutting element is radially expanded so that a portion thereof is radially outwardly spaced from the axis of the instrument. Once the cutting element is radially expanded, it is rotated about the axis to cut the tissue and create a peripheral boundary about the tissue specimen, to isolate the tissue specimen from surrounding tissue in the tissue region.

The invention, together with additional features and advantages thereof,

may best be understood by reference to the following description taken in conjunction with the accompanying illustrative drawing.

**Brief Description of the Drawing**

5

Fig. 1 is a perspective view of the distal end of one preferred embodiment of the inventive tissue retrieval instrument;

10

Fig. 2 is a perspective view illustrating the distal end of a monopolar embodiment of the inventive tissue retrieval instrument shown in Fig. 1;

15

Fig. 3 is a perspective view similar to that of Fig. 2, illustrating the distal end of a bipolar embodiment of the inventive tissue retrieval instrument shown in Fig. 1;

20

Fig. 4 is a cutaway view from the side illustrating the internal construction of a presently preferred proximal drive unit for operating the inventive tissue retrieval instrument;

25

Fig. 5 is a perspective view from the top illustrating the proximal drive unit of Fig. 4, with the top portion of the housing removed in order to show portions of its internal construction;

30

Fig. 6 is a perspective view from the proximal end illustrating the proximal drive unit of Figs. 4 and 5, with the top portion of the housing removed in order to show portions of its internal construction;

Fig. 7 is a perspective view from the distal end illustrating the proximal drive unit of Figs. 4-6, with the top portion of the housing removed in order to show portions of its internal construction;

Fig. 8 is a schematic view illustrating the distal end of the instrument of Fig. 1 disposed in a tissue region from which target tissue is to be retrieved, wherein the distal cutting element is deployed in a first position for isolating a first segment of a target tissue specimen from surrounding tissue;

5

Fig. 9 is a schematic view similar to Fig. 8, wherein the distal cutting element is deployed in a second position for isolating a second segment of the target tissue specimen from surrounding tissue;

10

Fig. 10 is a schematic view similar to Figs. 8 and 9, wherein the distal cutting element is deployed in a third position for isolating a third segment of the target tissue specimen from surrounding tissue;

15

Fig. 11 is a perspective view illustrating the distal end of a second preferred embodiment of the inventive tissue retrieval instrument;

20

Fig. 12 is a perspective cutaway view of the distal end of the embodiment of Fig. 11, illustrating the internal construction thereof, including tissue wrapping and cutting elements in their stored position;

25

Fig. 13 is a perspective cutaway view similar to that of Fig. 12, wherein the sheath has been retracted in order to deploy the tissue wrapping and cutting elements shown in Fig. 12;

Fig. 14 is a side schematic view of the distal end of the embodiment of Figs. 11-13, illustrating the deployment of the tissue wrapping and cutting elements shown in Fig. 12;

30

Fig. 15 is a perspective view illustrating the tissue wrapping and cutting elements of Figs. 12 and 14 in their fully deployed position;



Fig. 16 is a side view showing the deployed tissue wrapping and cutting elements after the distal end of the instrument has been rotated to twist the wrapping and cutting elements in order to wrap a target tissue sample;

5 Fig. 17 is a perspective, schematic view of an alternative embodiment of the distal end of the inventive tissue retrieval instrument, wherein the cutting element of the instrument is in a retracted position;

10 Fig. 18 is a perspective, schematic view similar to Fig. 17, illustrating the cutting element in a deployed position for creating cylindrical tissue segments; and

15 Fig. 19 is a perspective, schematic view similar to Figs. 17 and 18, illustrating the cutting element in a deployed position for creating tissue segments of varying heights.

#### **Description of the Invention**

Referring now more particularly to Fig. 1, there is shown the distal end 12 of a first preferred embodiment of an inventive tissue retrieval or biopsy instrument 10. The distal end 12 preferably comprises a disposable wand portion, including a distal tip 14. The tip 14 may comprise a conventional trocar tip, or, preferably, may include an electrosurgical (RF) element or wire 16 which may be energized by a conventional electrosurgical generator (not shown) in order to facilitate tissue cutting and consequent advancement of the instrument 10 to a predetermined tissue site in the patient's body.

25 Proximally of the tip 14 is a shaft 18, preferably lying along an axis 19 (Fig. 1) of the instrument, on which is disposed a cutting element or wire 20. This wire 20 is disposed axially along the length of the shaft 18 in its retracted position (not shown), but may be deployed radially outwardly, as shown in Fig. 1. 30 The element 20 is preferably comprised of a wire or rectangular band fabricated

of memory metal such as Nitinol, though stainless steel, tungsten, or other biocompatible materials could also be employed, if desired. The cutting element 20 acts as an electrosurgical cutter, energizable by means of RF energy provided by the electrosurgical generator discussed supra. The instrument 10 may be  
5 monopolar, as illustrated in Fig. 2, with the cutting element 20 comprising the active electrode and a return electrode spaced from the instrument 10 and most typically being disposed on the patient's skin in the form of a patch electrode on the thigh or back. Alternatively, the instrument 10 may preferably be bipolar, as illustrated in Fig. 3, with the cutting element comprising the active electrode and  
10 a return electrode 22 being disposed on the instrument in close proximity to the active electrode, such as along the shaft 18. With such an arrangement, a layer of insulation 23 is disposed between the return electrode (comprising a major portion of the surface area of the shaft 18) and the portion of the shaft adjacent to the active electrode, which receives the cutting element 20 in its retracted  
15 position. The bipolar embodiment is generally preferred because of a greater safety factor and lower power requirements.

A plurality of cutting wires 20 may be employed if desired, preferably spaced circumferentially about the shaft 18. In some embodiments, it may be preferably to have webs between the cutting elements, to create a "sail" rather  
20 than entire distinct separate cutting elements.

Referring now more particularly to Figs. 4-7, a proximal reusable driver portion 24 for the distal end or disposable wand portion 12 is shown. The driver portion 24 is preferably disposed on a stereotactic rail 26, in known fashion, for guidance of the instrument 10 to a predetermined tissue site using known  
25 imaging techniques. Such stereotactic imaging systems are available, for example, from Fischer, Inc. or Lorad, Inc. Alternative imaging systems, such as mammographic, ultrasonic, CT, MRI guidance systems may be used in place of a stereotactic system, if desired. Additionally, the instrument may be guided to the lesion site using an articulating arm system or manually, rather than on a  
30 stereotactic rail.

The reusable driver portion 24 comprises a housing 28 within which is disposed a coaxial arrangement comprising an outer sheath 30, the shaft 18, and a rod 32 which is attached at its distal end to the cutter element 20. A knob 34 is rotatably attached to the shaft 18 through a gearing system 35 to rotate the shaft 18 as desired, for the purpose of circumferentially orienting and rotating the cutting element 20. Three levers 36, 38, and 40 extend outwardly through slots 42, 44, and 46, respectively, in the side of the housing 28. The first lever 36 is actuatable to slide the sheath 30 axially both proximally and distally, for a purpose to be described hereinbelow. The second lever 38 is actuatable to move the shaft 18 axially in distal and proximal directions, as desired. The third lever 40 is actuatable to move the rod 32 axially in distal and proximal directions, as desired. Since the rod 32 is attached at its distal end to the proximal end of the wire cutter 20, movement of the rod 32 in an axial direction also causes the proximal end of the wire cutter 20 to move in an axial direction. Since the distal end of the cutter 20 is anchored to the shaft 18, movement of the proximal end of the cutter element 20 in a distal direction causes the midportion of the cutting element 20 to bow radially outwardly to a radially expanded position, as shown in any of Figs. 1-3, while movement of the proximal end of the cutter element 20 in a proximal direction causes the midportion of the cutter element 20 to retract radially to its stowed position, disposed linearly along the axial length of the shaft 18, preferably within a recess 48 (Fig. 1).

An advantageous feature of the invention is the employment of a series of stops 50 in the second slot 44, and a series of stops 52 in the third slot 46, as illustrated in Figs. 5-7. The stops 50 enable the second lever 38 to be actuated to a plurality of discrete axial positions, which in turn permits the shaft 18 to be actuated to a corresponding plurality of discrete axial positions for fine tuning the axial position of the electrosurgical cutting element 20. Similarly, the stops 52 enable the third lever 40 to be actuated to a plurality of discrete axial positions, which in turn permits the electrosurgical cutting element 20 to be radially extended to a corresponding plurality of radially extended positions, for a

purpose to be described more fully hereinbelow.

With reference now more particularly to Figs. 8-10, the operation of the first preferred embodiment of the inventive device will be explained. Initially, when it is determined that either a diagnostic or therapeutic biopsy procedure is indicated, the distal disposable wand portion 12 of the instrument 10 will be moved axially to a position wherein the distal tip is adjacent to and preferably within a target lesion 54, using the stereotactic rail 26 and associated imaging system. During this process step, wherein gross linear movement of the wand 12 is controlled by the rail system 26, the electrosurgical cutting element 16 on the distal tip 14 is energized to pierce and cut through the patient's body tissue 56 to permit distal advancement of the wand 12 to the region surrounding the lesion 54.

Once the distal tip 14 is generally in the desired position adjacent to or within the target lesion 54, using the stereotactic rail 26, the second lever 38 is actuated to provide fine tuning of the axial position of the distal tip 14 relative to the lesion 54, by moving the shaft 18 axially to a desired position, and securing the lever 38 in an appropriate stop 50 to maintain the desired axial position. This fine axial adjustment of the axial movement of the shaft 18 is performed using appropriate imaging equipment. The objective of this process step is to ensure that the distal end of the cutting wire 20 is disposed distally of the distal peripheral edge of the lesion 54, while at the same time the proximal end of the cutting wire 20 is disposed proximally of the proximal peripheral edge of the lesion 54. This will ensure the ability to isolate the entire lesion 54 during the cutting procedure, with sufficient margins to minimize the chance that any portion of the lesion inadvertently remains behind in the patient's body following removal thereof.

When the distal tip 14 is in the precise position desired by the practitioner, first lever 36, which is normally disposed in a first detent 58 (Figs. 5 and 6) in the first slot 42, is actuated proximally until it rests in a second detent 60 (Fig. 5) in the first slot 42. This action retracts the sheath 30 proximally a

sufficient distance to partially uncover the cutting element 20. It should be noted, however, that in some circumstances it may be desirable to fully retract the sheath, so that the entire cutting element 20 is released, in order to create a different cutting geometry. In such an instance, a detent 61 (Fig. 7) is provided within the slot 42 to accommodate the lever 36 in the fully proximal position necessary to achieve full axial retraction of the sheath. Additional intermediate detents 60 (not shown) may be provided to retract the sheath to intermediate positions corresponding to various partial radial extension positions of the cutting element.

After the sheath 30 is retracted as desired, the third lever 40 may then be actuated distally along the third slot 46 to an intermediate stop 52, thereby causing the rod 32, and therefore the proximal end of the cutting element 20, to move axially a distance equivalent to that traversed by the lever 40. This, of course, results in the partial radial expansion of the cutting element 20 to an arched or bowed configuration as shown in Fig. 8. The extended configuration of the cutting element 20 may define, when rotated about the instrument axis, a spherical cutting volume, as shown, or it may be configured to define an elliptical or toroidal cutting volume when the cutting element is rotated about the instrument axis 19, rather than a spherical volume.

Of course many other mechanisms for radially expanding the cutting element 20 may be utilized as well, within the scope of the invention. For example, since the wire 20 is preferably fabricated of a shaped memory or superelastic material, the proximal retraction of the sheath 30, and resultant release of the wire 20, may be sufficient to cause the cutting wire 20 to radially expand to its desired position.

Once the cutting element 20 is partially radially expanded as described supra, an inner portion of the target lesion 54 is isolated from surrounding tissue. To complete this step, the cutting element 20 is energized by the electrosurgical generator (not shown), after which the knob 34 is rotated, either manually or via a motorized drive mechanism, to rotate the cutting element 20 through a 360

degree arc. This rotational cutting action functions to completely sever the inner portion of the tissue sample from the surrounding tissue, thereby cutting off all blood supply to the inner tissue sample. Alternatively, if desired, the cutting element 20 may be simultaneously rotated and moved axially, by moving the shaft 18 axially, in order to create a "corkscrew"- shaped tissue segment.

Once this initial isolation step is completed, the cutting element or wire 20 is preferably further radially extended to the position shown in Fig. 9. This is accomplished by sliding the lever 36 proximally to another detent 60 to further proximally retract the sheath 30. Then, the third lever 40 may be axially slid distally to another stop or detent 52 to further radially extend the cutting wire 20. Once radially positioned, the cutting element 20 is energized by the electrosurgical generator, after which the knob 34 is rotated to rotate the cutting element 20 through a 360 degree arc. This rotational cutting action functions to completely sever a second segment of the tissue sample from the surrounding tissue, thereby cutting off all blood supply to this segment as well.

These steps may be repeated as many times as desired, in order to ensure that the tissue sample is segmented for efficient removal from the patient's body. Ultimately, however, a final cut is preferably made, by fully retracting the outer sheath 30, using the slide lever 36, and fully extending the cutting wire 20, using the slide lever 40, so that the cutting element 20 extends radially beyond the periphery of the target lesion 54, as illustrated in Fig. 10. The cutting element is then energized with RF energy, in the same manner as previously, after which the knob 34 is rotated to rotate the cutting wire 20 through a complete arc about the axis 19. At this point, the entire lesion 54 should be completely isolated from surrounding tissue, with a sufficient margin about the outer periphery thereof to ensure successful removal of the entire lesion.

During the foregoing segmentation process, if the cutting element 20 remains charged by RF energy during the stepwise radial extension process, the outer tissue rings will be further segmented radially.

Other segmentation approaches may be advantageously utilized as well, if

desired. For example, rather than segmenting the tissue sample circumferentially, from the inside out, the tissue sample may be segmented circumferentially from the outside in, i.e. by making an outer circumferential cut (Fig. 10), then partially retracting the cutting element 20 and cutting additional layers, as shown in Figs. 8 and 9. Alternatively, the tissue may be sectioned by extending and retracting the cutting element 20 radially, akin to "sectioning an orange". Additional radially oriented cutting elements could be employed as well to further segment the tissue.

An alternative approach to segmenting the tissue specimen to be retrieved is illustrated in the embodiment shown in Figs. 17-19. In this embodiment, wherein like elements to those in the embodiment of Fig. 1 are designated by like reference numerals, succeeded by the letter a, there is shown a tissue retrieval or biopsy instrument 10a, having a distal tip 14a with an electrosurgical element or wire 16a for cutting tissue and thereby permitting advancement of the instrument into a patient's body. A shaft or cannula 18a is disposed along an axis 19a of the instrument. A longitudinal slot 66 is disposed axially along a portion of the length of the cannula 18a. A cutting element or wire 20a, which is preferably an electrosurgical cutting element, is disposed so as to be extendable from and retractable into the slot. The cutting element is shown in a retracted position in Fig. 17, and in an extended position in Figs. 18 and 19.

In operation, once the instrument 10a has been positioned so that the distal tip is adjacent to a lesion to be removed, in the manner described supra with respect to the embodiment of Fig. 1, the cutting element 20a is charged with RF energy from a proximally disposed electrosurgical generator (not shown). Then, the cutting element 20a is radially extended by the practitioner, using a proximal control mechanism (not shown), to a position as shown, for example, in Fig. 18. Once extended, the cutting element is moved axially in a proximal direction along the slot 66, as illustrated by the arrow 68 and the phantom images of the cutting element 20a, in order to isolate a generally cylindrical tissue segment, as the cannula 18a is rotated about its axis 19a simultaneously.

Fig. 19 illustrates a procedure similar to that illustrated in Fig. 18, except that while the cutting element 20a is being axially moved in a proximal direction as shown by arrows 70, it is also deployed to various radial heights, in order to create a variable height cut.

5           Once segmentation of the tissue sample has been completed, whichever embodiment has been employed, each tissue segment can be withdrawn using a suitable retrieval apparatus. Preferably, the tissue segments are withdrawn through a cannula, such as the sheath 30, using such means as a suction grasper, flexible mechanical graspers, an auger conveyor, a prickly bristle or brush  
10           grasper, a wire retrieval basket, or the like.

          The foregoing procedure and apparatus may be used for either a diagnostic or a therapeutic purpose. It is particularly advantageous for a diagnostic procedure because the resultant incision from the procedure will not substantially exceed in length the diameter of the cannula. On the other hand, a  
15           second preferred embodiment, illustrated in Figs. 11-16, is particularly suited to a therapeutic procedure, wherein it is highly desired to ensure that the entire lesion of interest is removed in one step, without segmenting that lesion within the body. This approach emphasizes maximum safety, in that only a single  
20           procedure is necessary, assuming the tissue sample margins are clean, and the incision necessary to remove the intact tissue sample is of the minimum size necessary to remove the sample. With this procedure, there is also a somewhat reduced risk of cell migration from the specimen to the surrounding tissue, since as described below, the specimen is encapsulated as soon as it is isolated and then promptly removed. No segmentation of the specimen occurs within the patient's  
25           body.

          Referring now to Figs. 11-14, wherein like elements to those in the first embodiment are identified by like reference numerals, followed by the letter "b", there is shown the distal end or disposable wand portion 12b of an instrument 10b. The portion 12b includes a distal tip 14b, which may be constructed in a  
30           manner similar to that of tip 14 in Fig. 1, a shaft 18b, and a sleeve 30b. Disposed



in a radially retracted orientation in a recess 48b of the shaft 18b are a plurality of encapsulation elements or bands 72, one of which also comprises a single electrosurgical cutting element 20b. For the purposes of the invention it is unimportant which of the encapsulation elements 72 may be charged by means of RF energy to form an electrosurgical cutter, and in certain instances it may be advantageous to employ a plurality of cutting elements. Each of the encapsulation elements 72 and the cutting element 20b are attached at their distal ends to the distal end of the shaft 18b, at its connection with the distal tip 14b of the instrument 10b, which connection is preferably accomplished by means of a keyway 74.

The proximal end of the instrument 10b may be substantially the same as that for the instrument 10, illustrated in Figs. 4-7, comprising a reusable driver portion having an actuator for axially moving the sheath 30b between proximal and distal positions, a linear actuator for axially moving the shaft 18b, an actuator for rotationally moving the shaft 18b, and an actuator for axially moving the proximal ends of the encapsulation elements 72 and cutting element 20b, in order to radially extend and retract each of the elements 72 and 20b, as illustrated in Figs. 14-16.

In operation, as with the first embodiment of Fig. 1, when it is determined that either a diagnostic or therapeutic biopsy procedure is indicated, the distal disposable wand portion 12b of the instrument 10b will be moved axially to a position wherein the distal tip is adjacent to and distally of a target lesion, using the stereotactic rail 26 and associated imaging system. During this process step, wherein gross linear movement of the wand 12b is controlled by the rail system 26, the electrosurgical cutting element (not shown) on the distal tip 14b is energized to pierce and cut through the patient's body tissue to permit distal advancement of the wand 12b to the region surrounding the lesion.

Once the distal tip 14b is generally in the desired position adjacent to the target lesion, using the stereotactic rail 26, the second lever 38 is actuated to provide fine tuning of the axial position of the distal tip 14b relative to the lesion,

by moving the shaft 18b axially to a desired position, and securing the lever 38 in an appropriate stop 50 to maintain the desired axial position. This fine axial adjustment of the axial movement of the shaft 18b is performed using appropriate imaging equipment. The objective of this process step is to ensure that the distal end of the cutting wire 20b is disposed distally of the distal peripheral edge of the lesion, while at the same time the proximal end of the cutting wire 20b is disposed proximally of the proximal peripheral edge of the lesion. This will ensure the ability to isolate the entire lesion during the cutting procedure, with sufficient margins to minimize the chance that any portion of the lesion inadvertently remains behind in the patient's body following removal thereof.

When the distal tip 14b is in the precise position desired by the practitioner, first lever 36, which is normally disposed in a first detent 58 (Figs. 5 and 6) in the first slot 42, is actuated proximally until it rests in a second detent 60 (Fig. 7) in the first slot 42. This action retracts the sheath 30b proximally a sufficient distance to completely uncover the cutting element 20b and associated encapsulation elements 72. The third lever 40 may then be actuated distally along the third slot 46 to the distal-most stop 52, thereby causing the rod 32, and therefore the proximal ends of the cutting element 20a and encapsulation elements 72, to move axially a distance equivalent to that traversed by the lever 40. This, of course, results in the radial expansion of the cutting element 20b and encapsulation elements 72 to an arched or bowed configuration as shown in Fig. 14, wherein the cutting element 20b defines a peripheral boundary which lies radially beyond the peripheral boundary of the lesion, as in the case of the first embodiment shown in Fig. 8. Again, it should be noted that the cutting element and encapsulation elements need not be fully extended, especially if an ellipsoidal or toroidal cutting geometry is desired, in which case intermediate stop 61 is utilized.

Once the cutting element 20b and associated encapsulation elements 72 are radially expanded as described supra, it is time to isolate the target lesion from surrounding tissue. Advantageously, a spherical or toroidal tissue sample

having a radius of at least 15 mm may be defined and isolated by rotating the cutting element 20b about the axis of the shaft 18b. The encapsulation elements 72 will also be rotated during this process, but their function is not yet important. To complete the isolation step, the cutting element 20b is energized by the  
5     electrosurgical generator (not shown), after which the knob 34 is rotated, either manually or via a motorized drive mechanism, to rotate the shaft 18b, and thus the cutting element 20b through a 360 degree arc. This rotational cutting action functions to completely sever the tissue sample from the surrounding tissue, thereby cutting off all blood supply to the tissue sample (and thus from the lesion,  
10    which should be completely contained within the tissue sample).

After the isolation step is completed, the isolated tissue sample may be retrieved from the patient's body 56. This retrieval step may be accomplished in a number of ways, but it is the objective in connection with the illustrated embodiment to encapsulate and remove the isolated tissue sample in one piece.  
15    Accordingly, as is illustrated in Figs. 15 and 16, continued rotation of the shaft 18b, once the isolation step has been completed, preferably with the cutting element 20b de-energized, will twist and tighten the encapsulating elements 72 and the cutting element 20b about the tissue sample (not shown). As the shaft 18b is rotated, and the encapsulating elements 72 radially retracted and twisted,  
20    they will function to deform the tissue sample radially so that it is more compact and more securely retained within the spaced defined by the encapsulating elements 72.

Once the tissue sample has been fully encapsulated, the tissue sample may be removed from the patient's body. Advantageously, since the tissue sample is  
25    larger in cross-section than the cross-section of the sheath 30b, the inventors have developed an inventive approach for removal thereof which results in minimum trauma and incision size for the patient while still permitting the removal of an intact specimen. To remove the specimen, the sheath 30b is retracted proximally, following which the cutting element 20b is again energized by the electrosurgical  
30    generator. The shaft 18b, with the tissue specimen encapsulated thereabout, is

then proximally withdrawn by the practitioner, with the cutting element 20b functioning to cut through the tissue necessary to create a passage for exit of the sample. Once the unit, including the shaft and encapsulated tissue mass, is completely withdrawn from the body, the incision created by the cutting element 20b upon withdrawal from the body may be adhesively closed, with minimal required follow-up care and scarring.

Many alternative embodiments may be used to accomplish the method outlined supra, which essentially involves isolating the tissue mass from surrounding tissue, encapsulating the tissue mass in place about a shaft, then removing the encapsulated tissue mass and shaft from the body by energizing an RF electrosurgical cutter to cut its way out, without the need for a cannula or pre-existing incision. For example, a plurality of cutting elements could be employed, or a separate cutting element could be disposed on the shaft. An important aspect of the invention, of course, is a relatively high likelihood of acquiring the entire lesion of interest in a single therapeutic procedure, without the need for follow-up surgery.

While this invention has been described with respect to various specific examples and embodiments, it is to be understood that the invention is not limited thereto and that it can be variously practiced within the scope of the following claims.

What is Claimed is:

1. A biopsy instrument for retrieving body tissue, having a longitudinal axis and comprising:
  - a distal end adapted for entry into a patient's body; and
  - a cutting element disposed on said instrument, said cutting element being
- 5 actuatable between a radially retracted position and a radially extended position, relative to said axis, and being movable in said radially extended position to isolate a desired tissue specimen from surrounding tissue by defining a peripheral margin about said tissue specimen.
2. The biopsy instrument as recited in Claim 1, wherein said cutting element is rotatable about said axis in said radially extended position to isolate said desired tissue specimen.
3. The biopsy instrument as recited in Claim 1, wherein said cutting element is movable axially in said radially extended position to isolate said desired tissue specimen.
4. The biopsy instrument as recited in Claim 1, said distal end comprising an electrosurgical cutting element for cutting tissue and facilitating advancement of said instrument into the patient's body.
5. The biopsy instrument as recited in Claim 2, and further comprising a shaft disposed along said axis.
6. The biopsy instrument as recited in Claim 5, wherein said cutting element comprises an electrosurgical cutting element.

7. The biopsy instrument as recited in Claim 5, said instrument comprising a monopolar instrument wherein the electrosurgical cutting element comprises an active electrode thereof.

8. The biopsy instrument as recited in Claim 5, said instrument comprising a bipolar instrument wherein the electrosurgical cutting element comprises an active electrode thereof.

9. The biopsy instrument as recited in Claim 8, wherein a portion of said shaft comprises a return electrode of the bipolar instrument.

10. The biopsy instrument as recited in Claim 5, and further comprising a sheath which is axially movable between distal and proximal positions for selectively covering and uncovering the cutting element.

11. The biopsy instrument as recited in Claim 10, and further comprising a proximal driver unit for controlling radial expansion and retraction of said cutting element and rotation of said cutting element about said axis.

12. The biopsy instrument as recited in Claim 11, wherein the proximal driver unit further controls axial movement of said shaft and axial movement of said sheath.

13. The biopsy instrument as recited in Claim 5, wherein said cutting element may be manipulated to segment said tissue specimen after it has been isolated from the surrounding tissue.

14. The biopsy instrument as recited in Claim 13, wherein said cutting element segments said tissue specimen as it is being retracted from said radially extended position to said radially retracted position.

15. The biopsy instrument as recited in Claim 14, wherein said radially extended position comprises a first radially extended position, and said cutting element is further actuatable to a plurality of additional radially extended positions, said cutting element being rotatable about said axis in each of said  
5 radially extended positions to selectively peripherally segment said tissue specimen.

16. The biopsy instrument as recited in Claim 13, and further comprising a cannula having a lumen for providing a passageway into the patient's body, the segments of said tissue specimen being removable from the patient's body through said cannula.

17. The biopsy instrument as recited in Claim 5, wherein said instrument further comprises an element for encapsulating said tissue specimen so that it may be withdrawn as a single unit from the patient's body.

18. The biopsy instrument as recited in Claim 17, wherein said encapsulating element comprises a band disposed along said shaft, said band being actuatable between a radially retracted position and a radially extended position.

19. The biopsy instrument as recited in Claim 17, wherein said encapsulating element comprises a plurality of bands disposed along said shaft, each of said bands being actuatable between a radially retracted position and a radially extended position.

20. The biopsy instrument as recited in Claim 19, wherein said cutting element comprises one of said encapsulating elements.

21. An instrument for retrieving body tissue, having a longitudinal

axis and comprising:

a distal end adapted for entry into a patient's body; and

an element for encapsulating a tissue specimen so that it may be

5 withdrawn as a single unit from the patient's body.

22. The instrument as recited in Claim 21, wherein said encapsulating element comprises an axially disposed band, said band being actuatable between a radially retracted position and a radially extended position.

23. The biopsy instrument as recited in Claim 21, wherein said encapsulating element comprises a plurality of bands disposed along said axis, each of said bands being actuatable between a radially retracted position and a radially extended position.

24. The biopsy instrument as recited in Claim 23, wherein said instrument is rotatable about said axis in order that said bands may be twisted for encapsulating said tissue specimen.

25. The biopsy instrument as recited in Claim 21, and further comprising an axially disposed cutting element, the cutting element being actuatable between a radially retracted position and a radially extended position, and being rotatable about said axis in said radially extended position to isolate a  
5 desired tissue specimen from surrounding tissue by defining a peripheral margin about said tissue specimen.

26. The biopsy instrument as recited in Claim 25, wherein said cutting element comprises an electrosurgical cutting element.

27. The biopsy instrument as recited in Claim 21, and further comprising a sheath which is axially movable between distal and proximal



positions for selectively covering and uncovering the encapsulating element.

28. The biopsy instrument as recited in Claim 21, and further comprising a cutting element which is actuatable to cut tissue as said instrument is proximally withdrawn from said patient's body with said encapsulated intact tissue specimen.

29. A method for retrieving a tissue specimen from a patient's body, comprising the steps of:

5 inserting an instrument having a distal end, a longitudinal axis, and an axially disposed cutting element into the patient's body, so that the distal end is disposed in a tissue region from which the tissue specimen is to be taken;  
radially extending said cutting element so that a portion thereof is radially outwardly spaced from the axis of said instrument; and  
rotating said cutting element about said axis to cut said tissue and create a  
peripheral boundary about said tissue specimen, to isolate the tissue specimen  
10 from surrounding tissue in the tissue region.

30. The method as recited in Claim 29, and further comprising the step of encapsulating said tissue specimen.

31. The method as recited in Claim 30, wherein the encapsulating step includes the step of radially expanding at least one encapsulating element so that a portion thereof is radially outwardly spaced from the axis of said instrument and rotating said instrument about its axis so that said at least one encapsulating  
5 element encloses said tissue specimen.

32. The method as recited in Claim 31, wherein said at least one encapsulating element comprises a plurality of bands which are disposed axially along said instrument.

33. The method as recited in Claim 30, and further comprising the step of proximally withdrawing said instrument, with the encapsulated tissue specimen, from the patient's body, said step including the step of cutting tissue as the instrument is withdrawn.

34. The method as recited in Claim 29, and further comprising the step of segmenting said tissue specimen.

35. The method as recited in Claim 34, and further comprising the step of withdrawing each segment of said tissue specimen through a cannula lumen.


36. The method as recited in Claim 34, wherein the step of segmenting said tissue specimen includes the step of radially retracting said cutting element so that the tissue specimen is segmented radially.

37. The method as recited in Claim 34, wherein the step of segmenting said tissue specimen includes the steps of partially radially retracting said cutting element from its fully radially expanded position and rotating the instrument about its axis to cut said tissue and create a circumferential tissue segment.


5

38. The method as recited in Claim 37, wherein the segmenting step is repeated at differing partially radially expanded positions of the cutting element, so that a plurality of circumferential tissue segments are created.

39. The method as recited in Claim 29, and further comprising the step of simultaneously moving the cutting element axially as it is rotated about said axis to cut said tissue.



2/11






Fig. 4

4/11






Fig. 5

5/11




*Fig. 6*



6/11



*Fig. 7*




7/11

*Fig. 8**Fig. 9**Fig. 10*






10/11






*Fig. 15*



*Fig. 16*

11/11



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/04471

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61B10/00 A61B17/32 A61B17/22 A61B17/39

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 95 02371 A (SALIM) 26 January 1995  see page 2, line 5 - page 3, line 20 see page 5, line 2-28 see page 7, line 8 - page 8, line 3 ---	1-8, 13-15, 17-26
X	WO 95 02370 A (SALIM) 26 January 1995  see abstract; figures see page 2, line 1 - page 3, line 2 see page 5, line 31 - page 6, line 31 see page 11, line 12-34 ---  -/--	1-8, 13-15, 17-23, 25,26

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

4 June 1999

Date of mailing of the international search report

14/06/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Giménez Burgos, R

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 99/04471

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 195 28 440 A (KUEBLER) 6 February 1997 see the whole document ---	1-7, 13-16
X	GB 2 311 468 A (VALLEYLAB INC) 1 October 1997 see abstract; figures see page 3, line 32 - page 5, line 3 ---	1-6,8,9, 13-15
X	US 5 224 488 A (NEUFFER) 6 July 1993 see abstract; figures see column 1, line 49 - column 2, line 42 ---	1,2
X	EP 0 472 368 A (MED INSTITUTE, INC.) 26 February 1992 see abstract; figures 1,2 see column 1, line 47 - column 2, line 29 see column 5, line 2-37 -----	21,22

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 99/ 04471

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 29-39  
because they relate to subject matter not required to be searched by this Authority, namely:  
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.



FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-20

Biopsy instrument having a cutting element

2. Claims: 21-28

Surgical instrument having an element for encapsulating a tissue specimen

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/04471

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9502371	A	26-01-1995	AU 7191094 A	13-02-1995
WO 9502370	A	26-01-1995	AU 7190994 A	13-02-1995
DE 19528440	A	06-02-1997	NONE	
GB 2311468	A	01-10-1997	CA 2200029 A	27-09-1997
			DE 19706751 A	02-10-1997
			FR 2746628 A	03-10-1997
US 5224488	A	06-07-1993	NONE	
EP 0472368	A	26-02-1992	US 5100423 A	31-03-1992
			AT 124231 T	15-07-1995
			AU 643552 B	18-11-1993
			AU 8267591 A	27-02-1992
			CA 2049146 A	22-02-1992
			DE 69110794 D	03-08-1995
			DE 69110794 T	07-12-1995
			ES 2073687 T	16-08-1995
			JP 5137729 A	01-06-1993

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

### **IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**